

	B4 (197 hp) auit	B6 AWD (300 hp) auit	"Plug-in hybrids" T6 AWD (350 hp) auit	"Plug-in hybrids" T8 AWD (455 hp) auit
ENGINE				
Engines	B420T5	B420T	B4204T52	B4204T56
Type	In-line, 4 cyl. turbocharged	In-line, 4 cyl. supercharged and turbocharged	In-line, 4 cyl. Turbocharged with e-boost	In-line, 4 cyl. Turbocharged with e-boost
Configuration	FWD	AWD	AWD	AWD
Displacement	1969 cm³	1969 cm³	1969 cm³	1969 cm³
Bore	82,0 mm	82,0 mm	82,0 mm	82,0 mm
Stroke	93,2 mm	93,2 mm	93,2 mm	93,2 mm
Engine cylinder block material	Aluminium	Aluminium	Aluminium	Aluminium
Cylinder head material	Aluminium	Aluminium	Aluminium	Aluminium
Compression ratio	12.0:1	9.0:1	10,3:1	10,3:1
Valves, no/cylinder	4 ea.	4 ea.	4 ea.	4 ea.
Came shafts	2 ea.	2 ea.	2 ea.	2 ea.
DOHC/SOHC	DCHC	DCHC	DCHC	DCHC
Engine management system	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection	Gasoline direct injection
Ignition sequence	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2
Engine idling speed	800 rpm ± 75	800 rpm ± 75	850 rpm ± 50	850 rpm ± 50
Fuel, rec. Octane	95 - 98 RON	95 - 98 RON	95 - 98 RON	95 - 98 RON
Max engine speed	6000 rpm	6300 rpm	6000 rpm	6000 rpm
Max output	145 kW (197 hp) / 4750 - 5250 rpm	220 kW (300 hp) / 5400 rpm	186 kW (253 hp) / 5500 rpm	228 kW (310 hp) / 6000 rpm
Max torque	300 / 25 - 75 Nm / rps	420 / 35 - 80 Nm / rps	350 / 41 - 83 Nm / rps	400 / 50 - 80 Nm / rps
Battery type	-	-	Lithium-ion battery	Lithium-ion battery
Battery content, total amount of energy (kWh) (Nominal)	-	-	18,8	18,8
Battery content, total amount of energy (kWh) (Usable)	-	-	14,7	14,7
Battery charging time ^{**} , at 16A / 10A / 6A fuse (hours)	-	-	3.0 / 4.0 / 7.0	3.0 / 4.0 / 7.0
Battery charging time ^{***} , at 16A / 10A / 6A fuse (hours)	-	-	5.0 / 7.0 / 12	5.0 / 7.0 / 12
Battery placement	-	-	Centrally in the tunnel of the car	Centrally in the tunnel of the car
Electrical motor max power (kW)	10 kW	10 kW	107 kW	107 kW
Electrical motor max torque (Nm)	40 Nm	40 Nm	309 Nm	309 Nm
Driveline max power (kW)	-	-	107 kW and 186 kW ^{**} †	107 kW + 228 kW ^{**} †
Driveline max torque (Nm)	-	-	309 Nm and 350 Nm ^{**} †	309 Nm + 400 Nm ^{**} †
* Charging time can vary depending on vehicle climatization and other active electric loads in the vehicle. Charging time as well depends on e.g. ambient temperature				
^{**} AC 2-PHASE CHARGING TIME (200-240V), AC 2 phase only in EU				
^{***} AC 1-PHASE CHARGING TIME (200-240V)				
[†] 3 Up to				
TRANSMISSION				
Transmissions	7DCT EVO	-	-	-
First Gear	3,529	-	-	-
Second Gear	2,810	-	-	-
Third Gear	1,395	-	-	-
Fourth Gear	1,043	-	-	-
Fifth Gear	1,105	-	-	-
Sixth Gear	0,851	-	-	-
Seventh Gear	0,725	-	-	-
Eighth Gear	-	-	-	-
Reverse Gear	2,905	-	-	-
Automatic Gearbox/final drive	4.333 / 3.250	-	-	-
Transmissions (AWD)	-	AWF8G55	AW TG-81SD	AW TG-81SD
First Gear (AWD)	-	5,057	5,250	5,250
Second Gear (AWD)	-	3,070	3,029	3,029
Third Gear (AWD)	-	2,050	1,950	1,950
Fourth Gear (AWD)	-	1,520	1,457	1,457
Fifth Gear (AWD)	-	1,262	1,221	1,221
Sixth Gear (AWD)	-	1,000	1,000	1,000
Seventh Gear (AWD)	-	0,792	0,809	0,809
Eighth Gear (AWD)	-	0,661	0,673	0,673
Reverse Gear (AWD)	-	3,992	4,015	4,015
Automatic Gearbox / final drive (AWD)	-	3,075	3,075	3,075
PERFORMANCE				
Performance	Automatic	Automatic	Automatic	Automatic
Gearbox	7DCT EVO	AWF8G55	AW TG-81SD	AW TG-81SD
Acceleration, 0-100 km/h, sec	7,6 s	6,0	5,4	4,6
Top speed, km/h	180 km/h	180 km/h	180 km/h	180 km/h
WLTP "Low" l/100 km / CO ₂ g/km	8.9 - 9.5 l/100 km / 202 - 215 g/km	11.8 - 12.3 l/100 km / 267 - 278 g/km	-	-
WLTP "Medium" l/100 km / CO ₂ g/km	6.0 - 6.6 l/100 km / 136 - 149 g/km	7.8 - 8.6 l/100 km / 177 - 194 g/km	-	-
WLTP "High" l/100 km / CO ₂ g/km	5.2 - 5.8 l/100 km / 117 - 132 g/km	6.4 - 7.2 l/100 km / 145 - 162 g/km	-	-
WLTP "Extra High" l/100 km / CO ₂ g/km	6.1 - 7.0 l/100 km / 138 - 159 g/km	7.2 - 8.5 l/100 km / 162 - 185 g/km	-	-
WLTP Combined l/100 km / CO ₂ g/km	6.2 - 6.9 l/100 km / 140 - 156 g/km	7.7 - 8.5 l/100 km / 174 - 192 g/km	0.7 - 1.0 l/100 km / 17 - 23 g/km	0.7 - 1.0 l/100 km / 17 - 23 g/km
Electric Range [EAER] WLTP, City,	-	-	102 - 85 km	102 - 85 km
Electric Range [EAER] WLTP, Comb.	-	-	92 - 75 km	92 - 75 km
Electric Consumption (kWh/100 km)	-	-	16.3 - 18.8 kWh/100 km	16.3 - 18.8 kWh/100 km
DIMENSIONS EXTERIOR				
Length (L103)	4778 mm	4778 mm	4778 mm	4778 mm
Wheelbase (L101)	2872 mm	2872 mm	2872 mm	2872 mm
Front Overhang (L104)	855 mm	855 mm	855 mm	855 mm
Rear Overhang (L105)	1051 mm	1051 mm	1051 mm	1051 mm
Height (including shark fen) (at curb weight) (H101)	1437 mm	1437 mm	1430 mm	1430 mm
Height (including shark fen) (at curb weight + 1 person) (H101)	1432 mm	1432 mm	1427 mm	1427 mm
Height with open tailgate/trunklid (H110)	1954 mm	1954 mm	1954 mm	1954 mm
Width (Body width) (W103)	1850 mm	1850 mm	1850 mm	1850 mm
Width (mirrors folded) (W145)	1916 mm	1916 mm	1916 mm	1916 mm
Width (including mirrors, outer edge) (W144)	2040 mm	2040 mm	2040 mm	2040 mm
Width (Body width) (W116)	1850 mm	1850 mm	1850 mm	1850 mm
Track, front (depending on rim size) (W101-1)	1593 mm - 1610 mm	1593 mm - 1610 mm	1593 mm - 1610 mm	1593 mm - 1610 mm
Track, front (depending on rim size) (W101-2)	1593 mm - 1610 mm	1593 mm - 1610 mm	1593 mm - 1610 mm	1593 mm - 1610 mm
DIMENSIONS INTERIOR				
Headroom without panoramic roof (front) (Maximum) (H62-1)	1019 mm	1019 mm	1019 mm	1019 mm
Headroom with panoramic roof (front) (Maximum) (H62-1 SR)	994 mm	994 mm	994 mm	994 mm
Headroom without panoramic roof (front/rear) (H61-1 / H61-2)	978 mm / 966 mm	978 mm / 966 mm	978 mm / 966 mm	978 mm / 966 mm
Headroom with panoramic roof (front/rear) (H61-1 SR / H61-2 SR)	949 mm / 967 mm	949 mm / 967 mm	949 mm / 967 mm	949 mm / 967 mm
Passenger compartment width at shoulder height (front/rear) (W3-1 / W3-2)	1425 mm / 1384 mm	1425 mm / 1384 mm	1425 mm / 1384 mm	1425 mm / 1384 mm
Leg room (front/rear) (L34 / L51-2)	1074 mm / 895 mm	1074 mm / 895 mm	1074 mm / 895 mm	1074 mm / 895 mm
Hip room (front/rear) (W5-1 / W5-2)	1404 mm / 1356 mm	1404 mm / 1356 mm	1404 mm / 1356 mm	1404 mm / 1356 mm
GROUND CLEARANCE				
Ground clearance (at curb weight) (H156)	148 mm	148 mm	144 mm	144 mm
Ground clearance (at curb weight + 1 person) (H156)	142 mm	142 mm	138 mm	138 mm
WADING CAPABILITY				
Wading capability depth at curb weight (at walking speed)	250 mm	250 mm	Up to a depth approximately level with the floor at walking speed	Up to a depth approximately level with the floor at walking speed
STEERING				
Steering ratio (angle/angle)	16,2	16,2	16,2	16,2
Turning circle (Curb to curb) (depending on rim size)	11,0 m - 11,7 m	11,0 m - 11,7 m	11,0 m - 11,7 m	11,0 m - 11,7 m
Turning circle (Wall to wall) (depending on rim size)	11,4 m - 12,1 m	11,4 m - 12,1 m	11,4 m - 12,1 m	11,4 m - 12,1 m
Turns of steering wheel end to end	3	3	3	3
CHASSIS AND BRAKES				
Suspension front	Double Wishbone Suspension, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Double Wishbone Suspension, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Double Wishbone Suspension, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar	Double Wishbone Suspension, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar
Suspension rear	Integral Axle with Transverse Composite Leaf Spring, Hydraulic Shock Absorbers, Stabilizer Bar	Integral Axle with Transverse Composite Leaf Spring, Hydraulic Shock Absorbers, Stabilizer Bar	Integral Axle with Transverse Composite Leaf Spring, Hydraulic Shock Absorbers, Stabilizer Bar	Integral Axle with Transverse Composite Leaf Spring, Hydraulic Shock Absorbers, Stabilizer Bar
Steering	Electric Power Assisted Rack and Pinion Steering	Electric Power Assisted Rack and Pinion Steering	Electric Power Assisted Rack and Pinion Steering	Electric Power Assisted Rack and Pinion Steering
Braking system	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)	Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA)
Brake disc diameter (front) (Brake: 16" / 17" / 18")	296 mm / 322 mm / 345 mm	296 mm / 322 mm / 345 mm	296 mm / 322 mm / 345 mm	296 mm / 322 mm / 345 mm
Brake disc diameter (rear) (Brake: 16" / 17")	302 mm / 320 mm	302 mm / 320 mm	302 mm / 320 mm	302 mm / 320 mm
Brake disc thickness (front) (Brake: 16" + 17" / 18")	28 mm / 30 mm	28 mm / 30 mm	28 mm / 30 mm	28 mm / 30 mm
Brake disc thickness (rear) (Brake: 16" / 17")	29 mm / 30 mm / 32 mm	12 mm / 20 mm	12 mm / 20 mm	12 mm / 20 mm
Braking distance 100-0 km/h	30 mm / 30 mm / 32 mm	35 m	35 m	35 m
VOLUMES				
Largest Luggage volume - First (V214-1) (Largest volume. Load height limited by the head lining. Front limited by vertical plane tangential to the rear side of the front seatback) Total (including V209)	1431 l	1431 l	1393 l	1393 l
Largest Luggage volume - Second (V214-2) (Second seat up. Load height limited by the headlining. Front limited by vertical plane tangential to the rear side of the front seatback) Total (including V209)	648 l	648 l	610 l	610 l
Open Luggage Compartment - First (V211-1) (Second seat folded. Load height limited to upper edge of the front window) Total (including V209)	888 l	888 l	850 l	850 l
Open Luggage Compartment - Second (V211-2) (Second seat up. Load height limited to the upper edge of the second seatback or second window) Total (including V209)	519 l	519 l	481 l	481 l
Luggage volume, Separate Storage Areas in Luggage Compartment. (V209) (Closed storage areas located around the luggage compartments, behind wheel arches, under the floor, or any other area) - without rep kit and recess B420T, B420T2, B420T5	47 l	47 l	-	-
Luggage volume, Separate Storage Areas in Luggage Compartment. (V209) (Closed storage areas located around the luggage compartments, behind wheel arches, under the floor, or any other area) - rep kit B420T, B420T2, B420T5	23 l	23 l	-	-
Luggage volume, Separate Storage Areas in Luggage Compartment. (V209) (Closed storage areas located around the luggage compartments, behind wheel arches, under the floor, or any other area) - spare wheel "Alli" / B4204T52 & B4204T56	61 / 9 l	61 / 9 l	61 / 9 l	61 / 9 l
LENGTHS				
Cargo length from the first seatback to the tailgate measured at - the height of the floor covering (L212-1)	1821 mm	1821 mm	1821 mm	1821 mm
Cargo length from the first seatback to the tailgate measured at - the top of the first seatback (L214-1)	1694 mm	1694 mm	1694 mm	1694 mm
Cargo length from the second seatback to the tailgate measured at - the height of the floor covering (L212-2)	1033 mm	1033 mm	1033 mm	1033 mm
Cargo length from the second seatback to the tailgate measured at - the top of the second seatback (L214-2)	815 mm	815 mm	815 mm	815 mm
HEIGHTS				
Cargo floor height to ground (curb weight) (H253)	611 mm	611 mm	611 mm	611 mm
Rear opening height (car center line) (H202)	644 mm	644 mm	644 mm	644 mm
Cargo height (rear wheel center and car center line) (H201)	731 mm	731 mm	731 mm	731 mm
WIDTHS				
Cargo floor width, min. (Wheelhouse Width – at Floor) (W201)	1038 mm	1038 mm	1038 mm	1038 mm
Rear opening width upper min (W205)	888 mm	888 mm	888 mm	888 mm
Rear opening width at floor, min (W207)	1064 mm	1064 mm	1064 mm	1064 mm
WEIGHT/MISCELLANEOUS				
Weight, kg (min-max, depending on setup) (Curb weight/MiRO)	1664 kg / 1734 kg	1810 kg / 1880 kg	1994 kg / 2064 kg	1994 kg / 2064 kg
Total Weight (Depending on type of engine, gearbox etc.)	2240 kg	2350 kg	2530 kg	2530 kg
Max trailer weight, Unbraked (Max)	750 kg	750 kg	750 kg	750 kg
Max trailer weight, Braked (Max)	1800 kg	2000 kg	2000 kg	2000 kg
Fuel tank, Petrol	60 l	60 l	60 l	60 l
Aerodynamics, (Cd)	0,29	0,29	0,29	0,29
Aerodynamics, (Frontal area)	2,23 m²	2,23 m²	2,23 m²	2,23 m²
Aerodynamics, (Cd*A)	0,65	0,65	0,65	0,65
Max roof load	75 kg	75 kg	75 kg	75 kg
* MiRO = Mass in Running Order				